

## Durable Design


- Stainless steel interior & exterior
- Coated evaporator coil
- 3 height adjustable, heavy duty, PE coated wire shelves
- LED interior lighting
- Digital temperature display
- Door lock with keys
- Simple plug-in installation
- Oversized bottom mount compressor section
- Door swing is field reversible with kit # KB-BLHK

## Energy Efficiency

- Self-closing door with stay open feature
- Seals tight with magnetic vinyl gasket
- Open door alert beeps when door has been open for 3 minutes.
- Foamed-in place high-density polyurethane insulated body, CFC-free
- Large evaporator & condenser for quick cooling and greater efficiency
- Bottom mount compressor provides energy savings and ease of service.

## Superior Quality

- Designed for mobility, reliability & efficiency in commercial kitchens
- Certified with ETL & Energy Star guaranteeing quality standards and energy efficiency.
- 4" swivel castors with 2 front brakes
- Easy grip handle
- Entirely self-contained system
- Automatic defrost system
- Digitally controlled temperature system
- Accommodates full-size bun sheet pans
- Easily adjustable shelf height
- Internal storage capacity is 18.9 cu. ft.
- NEMA 5-15 plug
- Compressor : Refrigerator - 1/3 HP / Freezer - 1/3 HP  
Holding temperature: Refrigerator 33°F to 39°F  
/ Freezer 5°F to -9.4°F



## Single Door Series Refrigerator & Freezer Bottom Mount Compressor KBSR-1 / KBSF-1



Project Name:

Location:

Item:


Qty:

Model:






5659 Royalmount Ave.  
Montreal, QC, Canada H4P 2P9  
Telephone: 514.737.9701 / Toll Free: 888.275.4538  
Fax: 514.342.3854 / Toll Free: 877.453.8832  
sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108  
Miami, FL, United States 33181  
Telephone: 786.600.4687 / Toll Free: 844.218.8477  
Fax: 786.661.4100



## Technical Drawings KBSR-1 & KBSF-1



Model Number	Description	Interior / Exterior	# of Shelves	Capacity (cubic ft)	External Dimensions w/handle (W x D x H in)	Internal Dimensions (W x D x H in)	Compressor Size	Voltage / Frequency	Amps	Working Temp	Refrigerant	Ship Weight (lbs)
KBSR -1	Bottom Mount Single Door Refrigerator	Stainless Steel	3	18.9	26.8 x 32.75 x 82.7	22.8 x 24.3 x 53.8	1/3	115V 60 HZ	6.0	33°F to 39°F	R134a	315
KBSF -1	Bottom Mount Single Door Freezer	Stainless Steel	3	18.9	26.8 x 32.75 x 82.7	22.8 x 24.3 x 53.8	1/3	115V 60 HZ	7.0	5°F to -9°F	R134a	328

These units are designed for maximum performance in an air-conditioned area of 75°F ambient temperature and 55% relative humidity. There must be adequate ventilation at the top, sides & rear of the unit for proper operation.



NEMA  
5-15P

Warranty: 36 months parts & labor.  
Additional 24 months on compressor (parts only)

KOOL-IT is a registered trademark of MVP Group.  
Specifications subject to change without notice.



5659 Royalmount Ave.  
Montreal, QC, Canada H4P 2P9  
Telephone: 514.737.9701 / Toll Free: 888.275.4538  
Fax: 514.342.3854 / Toll Free: 877.453.8832  
sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108  
Miami, FL, United States 33181  
Telephone: 786.600.4687 / Toll Free: 844.218.8477  
Fax: 786.661.4100